

Different model gauges to cover your specific needs

QC5 Series advanced Dry Coating Thickness Gauges are available in Ferrous, Non-Ferrous, and Combined (Auto base detection) models. Measure coatings (paint, varnish, lacquer, etc.) and platings (niquel, zinc, chrome, etc.) quickly, easily, and precisely, with instruments featuring 9 calibration modes, calibration memories, graphics, statistics, a memory to store up to 32000 readings, and much more.



Applications

- Measure coatings and platings
- Use for controls in production
- Check finished products
- Measure paint, varnish, lacquer
- Measure niquel, zinc, chrome
- Inspect galvanized steel
- Check OPC drum cartridges

Outstanding Features

- Measure over ferrous and non-ferrous bases
- 9 calibration modes
- dmq probes with CalTag technology
- Errors of 1 to 3%
- Continuous measurements up to 99 per minute
- Statistics
- Real time histogram graphics
- Large LCD display w/ LED backlight
- Memory for 32000 readings
- Transfer data to PC via USB (DL models)
- dmq DataCenter software
- High impact ABS enclosure w/ rubber sides
- Touch-Sense front panel
- Model upgrade licenses

6 Models



Complies with DIN EN ISO 2178,
ASTM D7091 and DIN EN ISO 2360

	QC5 <i>F</i>	QC5 <i>N</i>	QC5 <i>C</i>	QC5 <i>DLF</i>	QC5 <i>DLN</i>	QC5 <i>DLC</i>
User Friendly Interface	•	•	•	•	•	•
9 Calibration Modes (**)	•	•	•	•	•	•
Calibration Memories	•	•	•	•	•	•
Fast Mode 99 Readings Per Minute	•	•	•	•	•	•
Real time Histogram Graphics	•	•	•	•	•	•
Statistics	•	•	•	•	•	•
Ferrous Base	•			•		
Non-Ferrous Base		•			•	
Auto Base Detection (Combined)			•			•
Transfer values Data Logger (DL)				•	•	•

F = Ferrous
N = Non-Ferrous
C = Combined (Ferrous / Non-Ferrous)
DL = Data Logger

Technical Specifications

Measurement		User Interface	
Normal range	0-1500 μ m (0-60 mils)	Languages	English, Spanish and Portuguese
Error	± 1 to 3% or ± 1 to 3 μ m	Navigation	Menus and Icons
Resolution	Resolution: 1 μ m (0.1mil)	Personal ID	Personal data entry
Units	μ m (microns) and mils	Electronic Unit	
Calibration Modes (**)		Dimensions	78 x 117 x 24 mm
9 modes	B+P, 2PT, MPT, BSE, ONE, ISO, SSP, SWE, AUS	Weight	180g with batteries
Data Logger		Working Temp	-10° a +50°C
Capacity	32000 + Reading	Enclosure	High impact ABS with rubber sides
Organization	Up to 8 files with names	Power Supply	
Internal Clock	Record date and time	Batteries	2 x AA 1,5v
Capture modes	Manual and automatic	Battery life	100 hours w/backlight off
PC Connection		Battery Indicator	Permanent
Connection	USB	Shutdown	Manual, Auto or Continuous
Updates / Upgrades	Unit software / Model	Display	
Front Panel		Digits sizes	12 and 17mm tall (Easy-view)
Type	Touch-Sense	Backlight	LED (ON, OFF, AUTO)
Sensitivity	Adjustable	Contrast	Digital and adjustable
		LCD	Graphic LCD 128 x 64 px

Presentation

- QC5 electronic unit
- Straight (F, N, or C) probe
- Calibration base (F, N, or both)
- Set of 3 calibration shims
- USB cable to connect to PC
- dmeq DataCenter Software
- Printed user manual
- High impact carrying case
- Certificate of conformity

dmeq DataCenter Software

DataCenter is a universal program developed by Demeq that is used to download and process data in models with a Data Logger (DL). Values stored in the unit memory can be transferred to a PC via USB and with the tools in DataCenter you can generate statistics, graphics, export values to other programs, prepare custom reports and much more.



S.I. Instruments
256 South Rd. Hilton
South Australia 5033
Ph (08) 8352 5511

Instruments developed and manufactured by DEMEQ
Washington 3894 | C.A.B.A. 1430EVb | Argentina
Sales: +54 11 4542-7783 | Service: +54 11 4541-3647
E-mail: infodemeq@demeq.com | Website: www.demeq.com